



**2005 FORMULA 48 PC**  
**BLUE HULL**  
**HIN# TNRD3775E405**  
**TWIN CUMMINS QSM11-M (DIESEL)**

#### **STANDARD FEATURES**

##### **Exterior**

NMMA Yacht Certification • Transferable 5-Year Formula Guard Limited Protection Plan • Imron® Standard graphic & cockpit accent striping • Molded fiberglass & structural foam hull matrix • Chemically bonded & thru-bolted deck-to-hull joint • Custom gunwale w/1 1/2" stainless steel insert • Bow thruster • Integrated bow platform • Concealed anchor davit w/fiberglass chain locker • Electric windlass w/200' chain & polished stainless steel anchor • Concealed quick-disconnect coiled-hose freshwater anchor/transom wash-down system • Stainless hardware & 316L stainless welded rails • Stainless bowrail w/pennant staff and mid-level lifeline cables • Bomar® cabin venting hatch w/integrated OceanAir rollout SKYscreen & privacy shade • Eight stainless port lights w/screens • Nonskid deck & walk-around coverboards • Two Dri-Fast® foam deck sun pads w/316L stainless rails • Tinted, tempered curved-glass windshield w/center walk-thru, side vents & polished stainless steel frame • Windshield wipers w/washer system • Radar arch w/dual flag staff/mast light • Remote control halogen searchlight • Dual air horn • Full-width swim platform w/integrated hull guards, concealed 316L stainless steel swim ladder & swim rails • Transom shower w/single-lever temperature control • Molded fiberglass transom trunk w/pneumatic-assist hatch, line storage, fender rack & four fenders • 240V shorepower/50-amp cord w/Glendinning automatic extend, retract and storage system • City water connection w/Glendinning automatic hose retract & one-point water fill for freshwater tank and/or city water • Polished stainless steel transom hookups & dockside access cords for cable TV & telephone

##### **Cockpit**

Burl wood-finish instrument panels • Complete backlit instrumentation, domed w/chrome bezels • Rudder indicator • Bennett® trim tab switches & indicators • Ritchie® compass • Raymarine™ Tridata depth/speed/water temperature display • Raymarine GPS navigational system w/C80 color chart plotter • SeaKey Volvo Penta satellite communication/boat data/security system • VHF radio w/antenna • Electronic shift & throttle control • Power hydraulic steering w/Dino™ tilt genuine mahogany steering wheel • Illuminated waterproof accessory rocker switches w/E-T-A® circuit breakers • Under-dash locker • Auxiliary 12V outlet • Molded fiberglass in-dash deck access steps w/316L stainless handrail • Dash-mounted full-feature weatherproof Clarion® AM/FM/CD stereo w/640W amplification 6-disc CD changer • Four 300W 6"x9" 3-way marine-grade speakers w/subwoofer powered by a 250W amplifier • Sixteen polished stainless steel drink holders • Dual switch courtesy lighting located at dash & transom • Integral 316L stainless safety rails • Weather-resistant cockpit seating featuring Dri-Fast® foam & StarLite® XL synthetic marine panel construction • Twin command seating w/dual-position helm & companion seats w/center storage compartment • Curved, extended port lounge • Surround lounge seating aft w/fiberglass-lined storage & fold-away side sections • Integrated side-entry boarding steps • Aft sun lounge package w/two dual-height Corian® tables & filler cushions • Two coated Sunbrella® cockpit pillows • Matching port and starboard lockers for tables, canvas and PFDs • Molded fiberglass wetbar/beverage center w/flush Corian countertop, molded sink, 120V/12V refrigerator.



**2005 FORMULA 48 PC  
 BLUE HULL  
 HIN# TNRD3775E405  
 TWIN CUMMINS QSM11-M (DIESEL)**

<b>LOA</b>	<b>51' 0"</b>	<b>15.54 m</b>
<b>LOA Less Bow Platform</b>	<b>48' 0"</b>	<b>14.63 m</b>
<b>Maximum Beam</b>	<b>14' 0"</b>	<b>4.27 m</b>
<b>Approx. Weight</b>	<b>35,050 lbs</b>	<b>15,898 kg</b>
<b>Approx. Weight w/Hardtop</b>	<b>35,750 lbs</b>	<b>16,216 kg</b>
<b>Cabin Headroom</b>	<b>7' 0"</b>	<b>2.13 m</b>
<b>Guest Stateroom</b>	<b>5' 10"</b>	<b>1.78 m</b>
<b>Fuel Capacity</b>	<b>400 gal</b>	<b>1,514 L</b>
<b>Water Capacity</b>	<b>100 gal</b>	<b>378 L</b>
<b>Holding Tank Capacity</b>	<b>75 gal</b>	<b>284 L</b>
<b>Bridge Clearance (Light Load) &amp; Mast Light</b>	<b>15' 6"</b>	<b>4.60 m</b>
<b>Bridge Clearance (Light Load) w/Hardtop &amp; Mast Light</b>	<b>15' 6"</b>	<b>4.60 m</b>
<b>Draft</b>	<b>44"</b>	<b>1.12 m</b>
<b>Deadrise</b>	<b>18°</b>	<b>18°</b>

### **Engine**

Twin diesel engine installation • Motorized hatch lift • Integrated quick-access engine hatch • Courtesy lighting • Automatic fire extinguisher • Thru-bolted I-beam engine mounts • Remote 12V oil change system for engines, transmissions & generator • Engine raw water strainers/seacocks • Eco Sound EPS 1000™ underwater exhaust system • Two starting and two auxiliary marine batteries w/retainers • 160-amp battery charger • Low-noise rotary bilge blowers • Two automatic bilge pumps • Bilge high water alarm • Bennett® hydraulic trim tabs • Bronze rudders & struts • 12.6 KW diesel generator w/sound shield • 2" stainless steel Aquamet® 19 propeller shafts (2 1/4" with optional power) • 4-blade nibral props